



GeoChem
Industrial and Speciality Chemicals

Durocoat

ECONOMICAL GLOSS POLYMER SOLID FLOOR POLISH

DESCRIPTION

Durocoat is a white liquid, emulsion polish. Specially developed to give an economical gloss and floor wear characteristics.

APPLICATIONS (Usage Areas)

Durocoat can be used in all types of industrial and household surfaces such as vinyl, lino, cork, **sealed wood** and concrete surfaces.

DIRECTIONS FOR USE

Floor Preparation:

Remove all old sealers, waxes, finishes, soil, etc. by hand or machine scrubbing. Rinse thoroughly and allow to dry.

Application:

Apply in even, parallel strokes with a clean lambs-wool applicator, mop, brush or lint-free cloth. Two coats with 25 minutes drying between coats is recommended.

Maintenance:

Sweep or vacuum daily. Remove surface soil by damp or wet mopping where necessary.

Recoating:

Clean floor with neutral cleaner, rinse well and allow to dry. Apply as directed in application above.

BENEFITS

Economical
Versatile polymer
Low maintenance
Coverage 60-70m²

PRECAUTIONS

Durocoat must be applied correctly

- Do not use on unprepared floors
- Ensure floors are clean and dry
- Use clean tools and applicators
- Do not maintain with alkali detergents
- Keep out of the reach of children

EMERGENCY TREATMENT

Skin contact: Flush immediately with soap and water, wash contaminated clothing before reuse. If irritation develops, seek medical advice.

Eye contact: Rinse immediately with plenty of water for 15 minutes with eyelids held wide open. Seek medical advice.

Inhalation: Move person to fresh air and seek medical advice.

Ingestion: Induce vomiting. Give 2 glasses of water to drink and seek immediate medical attention.

STORAGE

Durocoat has a shelf life of two years. Once dispensed use immediately.

Conditions to avoid:

Temperatures above 30C

Incompatible materials:

Strong acids and alkali materials.